



## TECHNICAL FOLDER

## FILTERCEL CFA-W

### Specifications

<b>Code</b>	FP16202
<b>Name</b>	CFA-W
<b>Description</b>	PLEATED FILTER CELL

### Applications

Ventilation and conditioning in the pharmaceutical and photographic industry. Air treatment plants, filter walls. Spray booths.

### Sizes

dimensions	400x500x48	mm
weight	1,15	kg

### Technical data

filter medium composition	polyester	
frame material	galvanized sheet	
regeneration	yes	
max. working temperature	100	°C
max. working R.H.	100	%

### Funcional data

nominal air flow	1850	m <sup>3</sup> /h
initial pressure drop	80	Pa
final pressure drop	250	Pa
average gravimetric efficiency	90,8	%
dust holding capacity	196	g
classification (EN 779:2012)	G4	
classification (ISO 16890)	coarse 60	%
flame resistance	F1 - DIN.53438	

Rev. 00-18

#### GENERAL FILTER HEADQUARTER

Via Emilia, 23  
31038 Paese (TV), Italia  
Tel: +39 0422 4594  
Fax: +39 0422 459590  
www.generalfilter.com  
info@generalfilter.com

#### GENERAL FILTER ITALIA

Via Morgagni, 40 int. 7/8  
20010 Pogliano Milanese (MI), Italia  
Tel: +39 02 93550640  
Fax: +39 02 93255670  
Italia: sales.ita@generalfilter.com  
Estero: sales.int@generalfilter.com

#### GENERAL FILTER FRANCE

13 Avenue d'Aygu  
26200 Montelimar, France  
Tel: +33 987876598  
Fax: +33 987876599  
r.meucci@generalfilter.fr

#### GENERAL FILTER IBERICA

Calle Salamanca 21  
28500 Arganda del Rey, Madrid,  
España  
Tel: +34 91 8719046  
Fax: +34 91 8719054  
gefisa@generalfilter.com

#### GENERAL FILTER HAVAK

Sanayi Sitesi P. Blok No. 10  
Hosdere Mevkii  
34517 Esenyurt, Istanbul, Türkiye  
Tel: +90 212 623 0074  
Fax: +90 212 623 0075  
info@generalfilterhavak.com