



TECHNICAL FOLDER

FILTERCEL CFA-W

Specifications

Code	FP24244
Name	CFA-W
Description	PLEATED FILTER CELL

Applications

Ventilation and conditioning in the pharmaceutical and photographic industry. Air treatment plants, filter walls. Spray booths.

Sizes

dimensions	592x592x98	mm
weight	3,45	kg

Technical data

filter medium composition	polyester	
frame material	galvanized sheet	
regeneration	yes	
max. working temperature	100	°C
max. working R.H.	100	%

Funcional data

nominal air flow	3790	m ³ /h
initial pressure drop	80	Pa
final pressure drop	250	Pa
average gravimetric efficiency	90,8	%
dust holding capacity	403	g
classification (EN 779:2012)	G4	
classification (ISO 16890)	coarse 60	%
flame resistance	F1 - DIN.53438	

Rev. 00-18

GENERAL FILTER HEADQUARTER

Via Emilia, 23
31038 Paese (TV), Italia
Tel: +39 0422 4594
Fax: +39 0422 459590
www.generalfilter.com
info@generalfilter.com

GENERAL FILTER ITALIA

Via Morgagni, 40 int. 7/8
20010 Pogliano Milanese (MI), Italia
Tel: +39 02 93550640
Fax: +39 02 93255670
Italia: sales.ita@generalfilter.com
Estero: sales.int@generalfilter.com

GENERAL FILTER FRANCE

13 Avenue d'Aygu
26200 Montelimar, France
Tel: +33 987876598
Fax: +33 987876599
r.meucci@generalfilter.fr

GENERAL FILTER IBERICA

Calle Salamanca 21
28500 Arganda del Rey, Madrid,
España
Tel: +34 91 8719046
Fax: +34 91 8719054
gefisa@generalfilter.com

GENERAL FILTER HAVAK

Sanayi Sitesi P. Blok No. 10
Hosdere Mevkii
34517 Esenyurt, Istanbul, Türkiye
Tel: +90 212 623 0074
Fax: +90 212 623 0075
info@generalfilterhavak.com