



## TECHNICAL FOLDER

## POLITEX INNER CART (IC)

### Specifications

<b>Code</b>	SF100W1
<b>Name</b>	INNER CART (IC)
<b>Description</b>	PAINT FILTERS

### Applications

Paint-stop effect in the painting sector.

### Sizes

dimensions	roll 1x10,38	m
------------	--------------	---

### Technical data

composition	double layer kraft paper with inertial effect	
regeneration	no	
thickness	65	mm
max. working temperature	180	°C
nominal weight	230-270	g/m <sup>2</sup>
advisable cross speed	0,75	m/s
initial pressure drop	30	Pa
final pressure drop	250	Pa
average gravimetric efficiency	79,5	%
dust holding capacity	5.000 - 15.000 (paint-stop)	g/m <sup>2</sup>
classification (EN 779:2012)	G2	
flame resistance	2 (U.L. 2-697A)	

Rev. 02\_12

#### GENERAL FILTER HEADQUARTER

Via Emilia, 23  
31038 Paese (TV), Italia  
Tel: +39 0422 4594  
Fax: +39 0422 459590  
www.generalfilter.com  
info@generalfilter.com

#### GENERAL FILTER ITALIA

Via Morgagni, 40 int. 7/8  
20010 Pogliano Milanese (MI), Italia  
Tel: +39 02 93550640  
Fax: +39 02 93255670  
Italia: sales.ita@generalfilter.com  
Estero: sales.int@generalfilter.com

#### GENERAL FILTER FRANCE

13 Avenue d'Aygu  
26200 Montlimar, France  
Tel: +33 987876598  
Fax: +33 987876599  
r.meucci@generalfilter.fr

#### GENERAL FILTER IBERICA

Calle Salamanca 21  
28500 Arganda del Rey, Madrid,  
España  
Tel: +34 91 8719046  
Fax: +34 91 8719054  
gefisa@generalfilter.com

#### GENERAL FILTER HAVAK

Sanayi Sitesi P. Blok No. 10  
Hosdere Mevkii  
34517 Esenyurt, Istanbul, Türkiye  
Tel: +90 212 623 0074  
Fax: +90 212 623 0075  
info@generalfilterhavak.com