



TECHNICAL FOLDER

POLITEX PA8H

Specifications

Code	SF8HR1
Name	PA8H
Description	PAINT FILTERS

Applications

Paint-stop effect in the painting sector.

Sizes

dimensions	roll 1,14x9,5	m
------------	---------------	---

Technical data

composition	different layes of expanded paper and polyester	
regeneration	no	
nominal thickness	30	mm
max. working temperature	80	°C
max. working R.H.	100	%
nominal weight	340	g/m ²
advisable cross speed	A=0,5 B=1 C=1,5	m/s
initial pressure drop	A=16 B=38 C=72	Pa
final pressure drop	250	Pa
efficiency	A=99,5-99,9 B=98,5-99,2 C=95-96	%
dust holding capacity	A=16080 B=13820 C=2770	g/m ²
flame resistance	2 (U.L. 2-697A)	

Rev. 02_14

GENERAL FILTER HEADQUARTER

Via Emilia, 23
31038 Paese (TV), Italia
Tel: +39 0422 4594
Fax: +39 0422 459590
www.generalfilter.com
info@generalfilter.com

GENERAL FILTER ITALIA

Via Morgagni, 40 int. 7/8
20010 Pogliano Milanese (MI), Italia
Tel: +39 02 93550640
Fax: +39 02 93255670
Italia: sales.ita@generalfilter.com
Estero: sales.int@generalfilter.com

GENERAL FILTER FRANCE

13 Avenue d'Aygu
26200 Montelimar, France
Tel: +33 987876598
Fax: +33 987876599
r.meucci@generalfilter.fr

GENERAL FILTER IBERICA

Calle Salamanca 21
28500 Arganda del Rey, Madrid,
España
Tel: +34 91 8719046
Fax: +34 91 8719054
gefisa@generalfilter.com

GENERAL FILTER HAVAK

Sanayi Sitesi P. Blok No. 10
Hosdere Mevkii
34517 Esenyurt, Istanbul, Türkiye
Tel: +90 212 623 0074
Fax: +90 212 623 0075
info@generalfilterhavak.com