



## TECHNICAL FOLDER

## POLITEX PA8S

### Specifications

<b>Code</b>	SF8SR1
<b>Name</b>	PA8S
<b>Description</b>	PAINT FILTERS

### Applications

Paint-stop effect in the painting sector.

### Sizes

dimensions	roll 1,14x9,5	m
------------	---------------	---

### Technical data

composition	different layer paper	
regeneration	no	
nominal thickness	25	mm
max. working temperature	80	°C
max. working R.H.	100	%
nominal weight	340	g/m <sup>2</sup>
advisable cross speed	A=0,5 B=1 C=1,5	m/s
initial pressure drop	A=5 B=13 C=25	Pa
final pressure drop	250	Pa
efficiency	A=98,5-99,5 B=97-98 C=94-95	
dust holding capacity	A=16350 B=15270 C=3980	g/m <sup>2</sup>
flame resistance	2 (U.L. 2-697A)	

### Notes

A=solvent paint B=water-soluble paint C=cellulose nitrate paint

Rev. 02\_14

#### GENERAL FILTER HEADQUARTER

Via Emilia, 23  
31038 Paese (TV), Italia  
Tel: +39 0422 4594  
Fax: +39 0422 459590  
www.generalfilter.com  
info@generalfilter.com

#### GENERAL FILTER ITALIA

Via Morgagni, 40 int. 7/8  
20010 Pogliano Milanese (MI), Italia  
Tel: +39 02 93250640  
Fax: +39 02 93255670  
Italia: sales.ita@generalfilter.com  
Estero: sales.int@generalfilter.com

#### GENERAL FILTER FRANCE

13 Avenue d'Aygu  
26200 Montelimar, France  
Tel: +33 987876598  
Fax: +33 987876599  
r.meucci@generalfilter.fr

#### GENERAL FILTER IBERICA

Calle Salamanca 21  
28500 Arganda del Rey, Madrid,  
España  
Tel: +34 91 8719046  
Fax: +34 91 8719054  
gefisa@generalfilter.com

#### GENERAL FILTER HAVAK

Sanayi Sitesi P. Blok No. 10  
Hosdere Mevkii  
34517 Esenyurt, Istanbul, Türkiye  
Tel: +90 212 623 0074  
Fax: +90 212 623 0075  
info@generalfilterhavak.com