



## TECHNICAL FOLDER

## FILTERCEL WRE

### Specifications

<b>Code</b>	WE16162
<b>Name</b>	WRE
<b>Description</b>	PLEATED FILTER CELL

### Applications

Air treatment plants. High flow rate plants. Pre-filtration and separation of particulates wherever minimum obstructions are required.

### Sizes

dimensions	394x394x47	mm
weight	0,44	kg

### Technical data

filter medium composition	polyester	
structure	punched cardboard	
regeneration	no	
max. working temperature	90	°C
max. working R.H.	100	%

### Funcional data

nominal air flow	930	m <sup>3</sup> /h
initial pressure drop	70	Pa
final pressure drop	250	Pa
average gravimetric efficiency	90	%
dust holding capacity	65	g
classification (EN 779:2012)	G4	
flame resistance	F1 - DIN.53438	

Rev. 01\_12

#### GENERAL FILTER HEADQUARTER

Via Emilia, 23  
31038 Paese (TV), Italia  
Tel: +39 0422 4594  
Fax: +39 0422 459590  
www.generalfilter.com  
info@generalfilter.com

#### GENERAL FILTER ITALIA

Via Morgagni, 40 int. 7/8  
20010 Pogliano Milanese (MI), Italia  
Tel: +39 02 93550640  
Fax: +39 02 93255670  
Italia: sales.ita@generalfilter.com  
Estero: sales.int@generalfilter.com

#### GENERAL FILTER FRANCE

13 Avenue d'Aygu  
26200 Montelmar, France  
Tel: +33 987876598  
Fax: +33 987876599  
r.meucci@generalfilter.fr

#### GENERAL FILTER IBERICA

Calle Salamanca 21  
28500 Arganda del Rey, Madrid,  
España  
Tel: +34 91 8719046  
Fax: +34 91 8719054  
gefisa@generalfilter.com

#### GENERAL FILTER HAVAK

Sanayi Sitesi P. Blok No. 10  
Hosdere Mevkii  
34517 Esenyurt, Istanbul, Türkiye  
Tel: +90 212 623 0074  
Fax: +90 212 623 0075  
info@generalfilterhavak.com