



**TECHNICAL FOLDER**

**FILTERCEL HT9**

**Specifications**

<b>Code</b>	H924242
<b>Name</b>	HT9
<b>Description</b>	PLEATED FILTER CELL

**Applications**

Spray booths and paint drying oven filtration.Pre-filtration and filtration with temperature up to 300°C.

**Sizes**

dimensions	592x592x48	mm
------------	------------	----

**Technical data**

filter medium composition	glass microfiber
frame material	galvanized sheet
regeneration	no
max. working temperature	300 °C
max. working R.H.	90 %

**Funcional data**

nominal air flow	1000	m <sup>3</sup> /h
initial pressure drop	265	Pa
final pressure drop	300	Pa
colorimetric efficiency	95	%
classification (EN 779:2012)	F9	
classification (ISO 16890)	ePM1 80	%
flame resistance	2 (U.L.)	

Rev. 00\_18

**GENERAL FILTER HEADQUARTER**

Via Emilia, 23  
31038 Paese (TV), Italia  
Tel: +39 0422 4594  
Fax: +39 0422 459590  
www.generalfilter.com  
info@generalfilter.com

**GENERAL FILTER ITALIA**

Via Morgagni, 40 int. 7/8  
20010 Pogliano Milanese (MI), Italia  
Tel: +39 02 93550640  
Fax: +39 02 93255670  
Italia: sales.ita@generalfilter.com  
Estero: sales.int@generalfilter.com

**GENERAL FILTER FRANCE**

13 Avenue d'Aygu  
26200 Montlimar, France  
Tel: +33 987876598  
Fax: +33 987876599  
r.meucci@generalfilter.fr

**GENERAL FILTER IBERICA**

Calle Salamanca 21  
28500 Arganda del Rey, Madrid,  
España  
Tel: +34 91 8719046  
Fax: +34 91 8719054  
gefisa@generalfilter.com

**GENERAL FILTER HAVAK**

Sanayi Sitesi P. Blok No. 10  
Hosdere Mevkii  
34517 Esenyurt, Istanbul, Türkiye  
Tel: +90 212 623 0074  
Fax: +90 212 623 0075  
info@generalfilterhavak.com