

TECHNICAL FOLDER
POLITEX A55V
Specifications

Code	SF560GR4
Name	A55V
Description	SYNTHETIC FILTER MEDIA

Applications

Spray booths. Pre-filtration and separation of coarse and finer particulate.

Sizes

dimensions	roll 2x20	m
------------	-----------	---

Technical data

composition	polyester fiber with polyamide grid on the air-exit side	
regeneration	no	
nominal thickness	22-25	mm
max. working temperature	100	°C
max. working R.H.	90	%
nominal weight	580	g/m ²
advisable cross speed	0,25	m/s
initial pressure drop	40	Pa
final pressure drop	450	Pa
colorimetric efficiency	>40	%
dust holding capacity	453	g/m ²
classification (EN 779:2012)	M5	
classification (ISO 16890)	ePM10 50	
flame resistance	F1 - DIN.53438	

Rev. 00_16

GENERAL FILTER HEADQUARTER

Via Emilia, 23
 31038 Paese (TV), Italia
 Tel: +39 0422 4594
 Fax: +39 0422 459590
 www.generalfilter.com
 info@generalfilter.com

GENERAL FILTER ITALIA

Via Morgagni, 40 int. 7/8
 20010 Pogliano Milanese (MI), Italia
 Tel: +39 02 93550640
 Fax: +39 02 93255670
 Italia: sales.ita@generalfilter.com
 Estero: sales.int@generalfilter.com

GENERAL FILTER FRANCE

13 Avenue d'Aygu
 26200 Montlimar, France
 Tel: +33 987876598
 Fax: +33 987876599
 r.meucci@generalfilter.fr

GENERAL FILTER IBERICA

Calle Salamanca 21
 28500 Arganda del Rey, Madrid,
 España
 Tel: +34 91 8719046
 Fax: +34 91 8719054
 gefisa@generalfilter.com

GENERAL FILTER HAVAK

Sanayi Sitesi P. Blok No. 10
 Hosdere Mevkii
 34517 Esenyurt, Istanbul, Türkiye
 Tel: +90 212 623 0074
 Fax: +90 212 623 0075
 info@generalfilterhavak.com